

## GCDB 300100

### 80.00 Chains

Set a stone, 14x10x8-inch, 9 inches in the ground, corner to Sections 4, 5, 32, 33, marked with 2 notches on W. and 4 notches on E. edges.

From which

- A white fir, 24-inch diameter bears S5°W, 22 links, marked: T 31 S R 2 E S 5 B T
- A larch, 30-inch diameter bears S23°E, 11 links, marked: T 31 S R 2 E S 4 B T
- A larch, 48-inch diameter bears N30°E, 44 links, marked: T 30 S R 2 E S 33 B T
- A larch, 6-inch diameter bears N37°W, 68 links, marked: T 30 S R 2 E S 32 B T

Surveyed by Peter Applegate - August 3, 1891

### RETRACEMENT

From the corner of Sections 3, 4, 33 and 34. West, between Sections 4 and 33.

**40.20** Fall 60 links S. of ¼ Section corner.

**80.41** Fall 133 links S. of Corner of Sections 4, 5, 32 and 33.

From the corner of Sections 4, 5, 32 and 33. West, between Sections 5 and 32.

**40.31** Fall 69 links S. of ¼ Section Corner.

**80.47** Fall 123 links S. of Corner of Sections 5, 6, 31 and 32.

**SEE NEXT PAGE FOR RE-ESTABLISHMENT OF CORNER**

**RE-ESTABLISHMENT  
SECTIONS 32 AND 33 ONLY  
GCDB 300100**

**78.77**

A point 40.00 chains in departure from the ¼ Section corner of Section 33 only, previously described.

Set an iron post, 3 feet long 2-inch diameter, 27 inches in the ground, for corner of Sections 32 and 33 only, with brass cap marked:

T30S R2E	
S32	S33
-----	
T31S R2E	
S4	
1937	

From which:

- A white fir, 22-inch diameter bears N.52°E., 57 links distance, marked: T 30 S R 2 E S 33 BT.
- A white fir, 40-inch diameter bears N.33°W., 67 links distance. Marked: T 30 S R 2 E S 32 BT.

**80.42**

To the original corner of Sections 4, 5, 32, and 33, which is a sandstone, 16x12x10-inch firmly set, marked with four notches on W. edge.

Date of Re-establishment: 1937