

CORNER ESTABLISHMENT

GCDB 400100

80.0 Chains

Set a stone, 14x10x8-inch, 10 inches in the ground for corner to Section 3, 4, 33, & 34, marked with 3 notches on E. and 3 notches on W. edges.

From which:

- A larch, 96-inch diameter bears N.50°W., 11 links, marked T 30 S R 2 E S 33 BT.
- A larch, 24-inch diameter bears S.38°W., 69 links, marked T31 S R 2 E S 4 BT.
- A white fir, 24-inch diameter bears N.35°E., 31 links, marked T 30 S R 2 E S 34 BT.
- A white fir, 36-inch diameter bears S.10°E., 41 links, marked T 31 S R 2 E S 3 BT.

Surveyed by P. Applegate, August 3, 1891.

RETRACEMENT

From the corner of Sections 2, 3, 34 and 35. West, between Sections 3 and 34.

40.39 Fall 100 links S. of $\frac{1}{4}$ Section corner.

80.66 Fall 183 links S. of corner of Sections 3, 4, 33 and 34

SEE NEXT PAGE FOR RE-ESTABLISHMENT OF CORNER

**RE-ESTABLISHMENT
SECTIONS 33 AND 34 ONLY
GCDB 400100**

79.44

A point 40.00 chains in departure from the ¼ Section corner of Section 34 only, previously described.

Set an iron post, 3 feet long, 2-inch diameter, 27 inches in the ground, for corner of Sections 33 and 34 only, with brass cap marked:

T30S R2E
S33 S34

T31S R2E
S 3
1937

From which:

- A white fir, 55-inch diameter bears N.25°E., 52 links distance. Marked: **T30S R2E S34 BT.**
- A white fir, 55-inch diameter bears N.45°W., 30 links distance. Marked: **T30S R2E S33 BT.**

80.68

The original corner of Sections 3, 4, 33 and 34, which is a basalt stone 14x10x8-inch firmly set with no legible marks.

Surveyed by L. Carter in 1937.

SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT

**FIRST RE-ESTABLISHMENT
SECTIONS 33 AND 34 ONLY
GCDB 400100**

Section corner common to Sections 33 and 34 only, Township 30 South, Range 2 East, W.M.

Found projecting 6 inches, the 2-inch diameter iron pipe with GLO brass cap marked:

T30S R2E
S33 S34
T31S R2E
S3
1937

As recorded by L. Carter.

The single remaining original BT, a Shasta Red Fir, (Record: White Fir) now 56-inch diameter, scribed "30S R2E S34 BT" in partly exposed face bears N25°E, 32.83 feet to scribed face. Record: N25°E, 34.32 feet.

The brass cap corner of Sections 3 and 4 bears N87½°W, 82.73 feet. Record: N88°49'W, 81.84 feet.

Marked a new tree "C.S. BT":

- White Fir, 33-inch diameter bears N26¾°W, 48.63 feet to center of tree at lower blaze.

Corner lies about 1100 feet East of USFS wood line crossing marker on 30-inch diameter Fir alongside road.

May 22, 1978
B. Malotte
R. Frost

Edward McGinty
County Surveyor

V = 20°