

**GCDB 440100**

**40.00 Chains**

Set a stone, 14x14x3-inch, 10 inches in the ground, for  $\frac{1}{4}$  s. corner, marked  $\frac{1}{4}$  on N. side.

From which:

- A white fir, 40-inch diameter bears S.11°W., 12 links marked  $\frac{1}{4}$  S BT.
- A white fir, 10-inch diameter bears N.39°E., 28 links marked  $\frac{1}{4}$  S BT.

Surveyed by P. Applegate in 1891.

**RE-ESTABLISHMENT**

**39.43 Chains**

A point 40.00 chains in departure from the corner of Sections 34 and 35 only, previously described.

Set an iron post, 3 feet long, 1-inch diameter, 27 inches in the ground, for  $\frac{1}{4}$  **Section corner of Section 34 only**, with brass cap marked:

$\frac{1}{4}$  S 34  
—————  
1937

From which:

- A cedar, 35-inch diameter bears N.45°E., 64 links distance. Marked:  $\frac{1}{4}$  S 34 BT.
- A cedar, 25-inch diameter bears N.12°W., 99 links distance. Marked:  $\frac{1}{4}$  S 34 BT.

**40.40**

The original  $\frac{1}{4}$  Section corner of Sections 3 and 34, which is a sandstone, 25x15x4-inch, firmly set, marked  $\frac{1}{4}$  on N. face.

I now change this corner to refer to Section 3 only.

Surveyed by L. Carter in 1937.