

GCDB 500240

40.00 Chains

Set an iron post, 3 feet long, 1-inch diameter, 27 inches in the ground, for  $\frac{1}{4}$  Section corner, with brass cap marked:

$$\begin{array}{c} \frac{1}{4} \\ S27 \mid S26 \\ 1937 \end{array}$$

From which:

- A fir, 12-inch diameter bears S.85°E., 67 links distance. Marked:  $\frac{1}{4}$  S 26 BT.
- A fir, 16-inch diameter bears N.65°W., 51 links distance. Marked:  $\frac{1}{4}$  S 27 BT.

Surveyed by L. Carter in 1937.

**SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT**

**FIRST RE-ESTABLISHMENT**  
**GCDB 500240**

Quarter corner common to Sections 26 and 27, Township 30 South, Range 2 East, W.M.

Found at the corner position, exposed 10 ins., the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set by the GLO in 1937, marked:

¼  
S26 | S27    (S26 and S27 stamped in reverse)  
1937

Original bearing trees recorded by Carter and Dawson of the GLO in 1937, found with healed blazes and measured to center at base:

- W. Fir, now 25 ins. diam. brs. record; S 85° E, 44.2 ft.
- W. Fir, now 26 ins. diam. brs. N 61° W, 35.7 ft. record; N 65° W, 33.7 ft.

Mark new bearing trees "CS" "BT" and take measurements to center at lower blaze:

- W. Fir 9 ins. diam. brs. N 20° E, 50.1 ft.
- Cedar 14 ins. diam. brs. S 31½° W, 57.2 ft.

Corner lies approx 1.5 mi. northeasterly along Abbott Butte Trail from trailhead, then east approx. 50 ft.

July 18, 2012  
H. Durkee  
S. Beecher

Scott Fein  
Deputy Jackson County Surveyor

P. – 9  
V. – 16° 20'