

## ESTABLISHMENT

GCDB 540100

### 40.00 chains

A willow tree, 4 inches in diameter, marked  $\frac{1}{4}$  on North face for  $\frac{1}{4}$  s. corner.

From which:

- A white fir, 8-inch diameter bears N.53°W., 34 links marked  $\frac{1}{4}$  S BT.
- A white fir, 8-inch diameter bears S.33°E., 39 links marked  $\frac{1}{4}$  S BT.

Surveyed by P. Applegate in August 3, 1891.

## RETRACEMENT

From the corner of Sections 1, 2, 35, and 36 West, between Sections 2 and 35.

**40.00** Find no evidence of  $\frac{1}{4}$  Section corner.

**80.33** Fall 114 links S. of corner of Sections 2, 3, 34, and 35.

**SEE NEXT PAGE FOR RE-ESTABLISHMENT**

**RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 35 ONLY  
GCDB 540100**

**39.76**

A point 40.00 chains in departure from the corner of Sections 35 and 36 only previously described.

Set an iron post, 3 feet long, 1-inch diameter, 27 inches in the ground, for  $\frac{1}{4}$  Section corner of Section 35 only, with brass cap marked:

$\frac{1}{4}$  S 35  
——  
1937

From which:

- A white fir, 22-inch diameter bears N.89°E., 36 links distance. Marked:  $\frac{1}{4}$  S 35 BT.
- A white fir, 35-inch diameter bears N.49°W., 12 links distance. Marked:  $\frac{1}{4}$  S 35 BT.

**40.17** Proportionate measurement.

Set an iron post, 3 feet long, 1-inch diameter 27 inches in the ground for  $\frac{1}{4}$  Section corner of Section 2 only, with brass cap.

Surveyed by L. Carter in 1937

**SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT**

FIRST RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 35 ONLY  
GCDB 540100

South quarter corner common to Section 35 only, Township 30 South, Range 2 East, W.M.

Found bent over and buried, the 1x36-inch iron pipe with GLO brass cap set by L. Carter in 1937.

I replaced the above (where pipe enters the ground vertically) with a 1x36-inch galvanized iron pipe, set 32 inches in the ground with a 2½-inch bronze disc marked:

JACKSON COUNTY 1978  
T30S R2E  
35  
¼S —

Original bearing trees recorded by Carter found as follows:

- White Fir, 29-inch diameter, with healed single blaze bears Record: N89°E, 23.76 feet to center.
- Sawed White Fir stump, 40-inch diameter with healed blaze bears Record: N49°W, 7.92 feet to center.
- The (brass cap) ¼ corner of Section 2 bears N89¼°W, 25.87 feet. Record: N89°11'W, 27.06 feet.

I deposited original monument alongside corner and mark a new tree CS BT:

- Douglas Fir, 9-inch diameter bears N21¾°E, 41.87 feet to center of tree at lower blaze.

Corner lies on steep NE slope, at west edge of old skid trail about 100 feet south of location marker on 8-inch diameter fir alongside road.

May 8, 1978  
B. Malotte  
R. Frost

Edward McGinty  
County Surveyor

V = 19¾°