

GCDB 540300

40.01 Chains

Set an iron post, 3 feet long, 1-inch diameter, 18 inches in the ground to bedrock, and in a mound of stone to top for $\frac{1}{4}$ Section corner, with brass cap marked:

S 23
 $\frac{1}{4}$ S —
S 26
1937

From which:

- A cedar, 12-inch diameter bears N.83°E., 122 links distance. Marked: $\frac{1}{4}$ S 23 BT.
- A cedar, 10-inch diameter bears S.25°E., 95 links distance. Marked: $\frac{1}{4}$ S 26 BT.

Surveyed by L. Carter in 1937.

SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT

FIRST RE-ESTABLISHMENT
GCDB 540300

Quarter corner common to Sections 23 and 26, Township 30 South, Range 2 East, W.M.

Found at the corner position, exposed 8 ins., in a mound of stones, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set by the GLO in 1937, marked:

S23
¼—
S26
1937

Bearing trees recorded by Carter and Dawson of the GLO in 1937, found with healed blazes and measured to center at base:

- Cedar, now 42 ins. diam. brs. N 83° E, 79.2 ft. Record; 80.5 ft.
- Cedar, now 38 ins. diam. brs. record; S 25° E, 62.7 ft.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Cedar 10 ins. diam. brs. S 26½° W, 34.1 ft.

Corner lies approx. 2.25 mi northeasterly along Abbott Butte Trail from trailhead, then approx. 700 ft. east.

July 18, 2012
H. Durkee
S. Beecher

Scott Fein
Deputy Jackson County Surveyor

P. – 11
V. – 13°10'