

GCDB 640200

97 Chains

Set an iron post, 3 feet long, 1-inch diameter, 27 inches in the ground, for $\frac{1}{4}$ Section corner, with brass cap marked:

S 25
 $\frac{1}{4}$ S —
S 36
1937

From which:

- A hemlock, 14-inch diameter bears N.48°E., 18 links distance. Marked: $\frac{1}{4}$ S 25 BT.
- A yew, 12-inch diameter bears S.35°E., 16 links distance. Marked: $\frac{1}{4}$ S 36 BT.

Surveyed by L. Carter in 1937.

SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT

FIRST RE-ESTABLISHMENT

GCDB 640200

Quarter corner common to Sections 25 and 36, Township 30 South, Range 2 East, W.M.

Found at the corner position, exposed 8 inches and in a mound of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap set by L. Carter of the GLO in 1937 marked:

S25
¼S —
S36
1937

Single remaining original bearing tree recorded by L. Carter in 1937:

- A hemlock now 19-inch diameter with a partially healed blaze (no scribing on small opening to face) bears Record: N 48° E, 11.9 feet to center at base.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Hemlock 16-inch diameter bears S 72¼° E, 36.7 feet
- Hemlock 16-inch diameter bears S 65¾° W, 19.3 feet.

Corner lies approximately 200 feet northeasterly from spur road and approximately 75 feet northeasterly of small creek. C. Southeasterly.

May 7, 2007

H. Durkee
B. Beeman

Roger R. Roberts
Jackson County Surveyor

P. - 114
V. - 17°05'