

GCDB 700100

80.00 chains

Set a stone, 20x16x12, 15 inches in the ground for corner to Township 30 and 31 S., Ranges 2 & 3 E., marked with 6 notches on each edge, the NE, SE, NW, SW, corners.

From which:

- A red fir, 14-inch diameter, P. Applegate. S59°W, 34 links. Marked: T 31 S R 2 E S 1 BT.
- A red fir, 48-inch diameter, P. Applegate. N10°W, 55 links. Marked: T 30 S R 2 E S 36 BT.
- A red fir, 16-inch diameter, P. Applegate. N54°E, 65 links. Marked: T 30 S R 3 E S 31 BT.
- A red fir, 18-inch diameter, P. Applegate. S38°E., 40 links. Marked: T 31 S R 3 E S 6 BT.

Surveyed by: Peter Applegate under Contract No. 571 dated April 10, 1891.

SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT

FIRST RE-ESTABLISHMENT

GCDB 700100

The corner of Townships 30 and 31 S, Ranges 2 and 3 East, the position of which is determined by reference to the original bearing trees.

At this point set an iron post, 3 feet long, 3-inch diameter, 30 inches in the ground with brass cap marked:

T30S	
R2E	R3E
S36	S31

S1	S6
T31S	
1928	

From which, the original bearing trees:

- A red fir, 20-inch diameter bears N.54°E., 66 links distance, old blaze healed over, not opened.
- A red fir, 22-inch diameter bears S.38°E., 40 links distance, old blaze healed over, not opened.
- A red fir, 18-inch diameter bears S.59°W., 35 links distance, old blaze healed over, not opened.
- A red fir, 48-inch diameter bears N.10°W., 56 links distance, old blaze healed over, not opened.

Resurveyed by Herbert Raymond in 1928

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 700100

The corner of Townships 30 and 31 South, Ranges 2 and 3 East, W.M.

Found 3 ins. diam. iron post with a $3\frac{3}{4}$ ins. diam. brass cap, exposed 6 ins., per First Re-establishment dated 1928, marked:

U.S. GENERAL LAND OFFICE SURVEY

T30S	
R2E	R3E
S36	S31

S1	S6
T31S	
1928	

From which, bearing trees marked on the First Re-establishment found and measured to the center of tree at lower blaze:

- Red fir, 28 ins. diam. with healed double blazes, bears record N54°E, 43.56 ft.
- Red fir, 18 ins. diam., with healed double blazes, bears record S59°W, 23.10 ft.

Scribed a new bearing tree and measure to the center of tree at lower blaze:

- Fir, 28 ins. diam., scribed "CS" in the upper blaze and "BT" in the lower blaze, bears N77°W, 15.05 ft.

The corner falls on steep easterly facing slope.

November 21, 2017
J. Hall

Scott D. Fein
Jackson County Surveyor

V = 15°