

GCDB 700200

80.00 Chains

Set a basalt stone, 20x15x8-inch 15 inches in the ground for corner of Sections 25, 30, 31, and 36, marked with 5 notches on N. and 1 notch on S. Edge.

From which:

- A fir, 12-inch diameter bears N.14°E., 82 links distance. Marked: T 30 S R 3 E S 30 BT.
- A fir, 36-inch diameter bears S.76°E., 39 links distance. Marked: T 30 S R 3 E S 31 BT.
- A pine, 14-inch diameter bears S.28°W., 35 links distance. Marked: T 30 S R 2 E S 36 BT.
- A fir, 18-inch diameter bears N.22°W., 38 links distance marked T 30 S R 2 E S 25 BT.

Surveyed by Fred Mensch and Lincoln Wilkes in 1920.

RESURVEY

80.00 Chains

Set an iron post, 3 feet long, 2-inch diameter, 27 inches in the ground, for **corner of Sections 25 and 36 only**, with brass cap marked:

	T30S	
S25		T30
S36		R3E S31
	R2E	
	1928	

From which:

- A fir, 4-inch diameter bears S.44°W., 14 links distance. Marked: T 30 S R 2 E S 36 BT.
- A fir, 4-inch diameter bears N.16½°W., 24 links distance. Marked: T 30 S R 2 E S 36 BT.

Surveyed by H. Raymond in 1928.