

GCDB 700300

80.00 Chains

Set a basalt stone, 20x10x7-inch, 15 inches in the ground for corner of Sections 19, 24, 25, and 30, marked with 4 notches on N. and 2 notches on S. edge.

From which:

- A cedar, 16-inch diameter bears N.4°E., 73 links distance. Marked: T 30 S R 3 E S 19 BT.
- A fir, 6-inch diameter bears S.7°E., 47 links distance. Marked: T 30 S R 3 E S 30 BT.
- A fir, 6-inch diameter bears S.4°W., 65 links distance. Marked: T 30 S R 2 E S 25 BT.
- A cedar, 10-inch diameter bears N.13°W., 70 links distance. Marked: T 30 S R 2 E S 24 BT.

Surveyed by P. Applegate in 1891.

RESURVEY

76.13 Chains

Point 80.00 chains in northing from the corner of Sections 25 and 36 only.

Set an iron post, 3 feet long, 2-inch diameter, 26 inches in the ground, for **corner of Sections 24 and 25 only**, with brass cap marked

T 30 S		
24		T 30 S
—		R 3E
S 25		S 30
R 2 E		
1928		

From which:

- A fir, 42-inch diameter bears S.7°W., 50 links distance. Marked: T 30 S R 2 E S 25 BT.
- A cedar, 26-inch diameter bears N.13°W., 20 links distance. Marked: T 30 S R 2 E S 24 BT.

Surveyed by H. Raymond 1928.