


**FIRST RE-ESTABLISHMENT**

**GCDB 100140**

Quarter corner common to Section 36, Township 32 South, Range 2 West and Section 31, Township 32 South, Range 1 West, W.M.

At the corner, found a 15 x 12 x 6-inch stone (no marks discernible).

Replaced said stone with and deposited it alongside a 1 x 36-inch Galvanized iron pipe, set 30 inches in the ground with a 2½-inch diameter bronze cap marked:



From which, original bearing trees recorded by R. Moore in 1883 found:

- Fir snag, 24-inch diameter, containing scribed "T" and partial "B" in partly exposed lower face bears Record: S45°E, 6.60 feet to scribed face.
- The base of a tipped over fir, about 20-inch diameter bears Record: S54°W, 13.86 feet.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Yew, 8-inch diameter bears S37°E, 43.35 feet (13.21 m).
- Douglas Fir, 9-inch diameter bears S55°W, 31.8 feet (9.69 m).

Corner lies on Northeast slope at Westerly edge of old skid road and about 250 feet N20°E of location marker on 18-inch diameter fir, located alongside logging road, c. North-South.

May 5, 1982  
R. Frost  
R. Templin

Edward McGinty  
County Surveyor

V = 19°  
P. -64