FIRST RE-ESTABLISHMENT

GCDB 200300

Section corner common to Sections 19, 20, 29 and 30, Township 32 South, Range 1 West, W.M. $V = 19^{\circ}$

Found, for the corner, loose and leaning southerly, the 2½-inch (6.4 cm) diameter iron pipe with standard BLM brass cap marked:

Bearing trees marked by BLM in 1966 found and measurements taken to center of tree at blaze:

- Douglas Fir, 12-inch (30 cm) diameter with single healed blaze bears N10°E, 100.56 feet (30.65 m). Record: N10°E, 100.32 feet (30.58 m).
- Broken top Douglas Fir, 24-inch (61 cm) diameter with single healed blaze bears S51°E, 51.91 feet (15.82 m). Record: S52°E, 53.46 feet (16.29 m).
- White Fir, 13-inch (33 cm) diameter with single healed blaze bears \$73°W, 65.26 feet (19.89 m). Record: \$73°W, 62.70 feet (19.11 m).
- White Fir, 12-inch (30 cm) diameter containing scribe marks including "S19 BT" in partially exposed single face bears N20°W, 64.71 feet (19.72 m). Record: N20°W, 64.02 feet (19.51 m).

Original bearing trees recorded by R. Moore in 1883 found:

- Douglas Fir, snag, 46-inch (1.17 m) diameter with bark scribe marks including "BT" bears N26°E, 5.31 feet (1.62 m) to lower bark face. Record: N30°E, 5.94 feet (1.81 m).
- Douglas Fir, snag, 30-inch (76 cm) diameter with bark scribe marks including "S R1W S9" bears S58°E, 12.49 feet (3.80 m) to upper bark face. Record: S60°E, 13.86 feet (4.22 m).
- Fir stump 26-inch (66 cm) diameter bears \$3°W, 29.35 feet (8.95 m) to center. Record: \$3°W, 29.04 feet (8.85 m).
- Douglas Fir, snag, 36-inch (91 cm) diameter with bark scribe marks including "3 R1W BT" bears N34°W, 38.34 feet (11.69 m) to lower bark face. Record: N31°W, 38.28 feet (11.67 m).

Mark a new tree "CS" "BT":

• White Fir, 6-inch (15 cm) diameter bears S8°E, 43.16 feet (13.16 m) to center of tree at lower blaze.

Corner lies on a steep (80%) Westerly slope, about 1300 feet (395 m) East of location marker on 18-inch (46 cm) diameter Cedar, alongside road.

August 18, 1980

R. Frost Approved by: Edward McGinty
D. Danielsen County Surveyor