

## FIRST RE-ESTABLISHMENT

GCDB 240300

Quarter corner common to Section 20 and 29, Township 32 South, Range 1 West, W.M.

$V = 18\frac{1}{2}^\circ$

Found, the original 24 x 18 x 18-inch stone (tipped out) marked "¼" as recorded by R. Moore in 1883.

At the original position of said stone, I set a 1 x 36-inch Galvanized iron pipe 24 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975

T32S R1W

20

¼S —

29

The only remaining original BT, now a Fir (partial) stump shell about 24-inch diameter bears  
Record: N28°W, 9.9 feet to estimated face.

I mounded stones around corner, deposited original stone alongside as a memorial, and marked new trees C.S.

BT and took measurements to center of trees at lower blaze:

- White Fir, 8-inch diameter bears N4½°E, 33.88 feet.
- White Fir, 8-inch diameter bears N45½°W, 35.01 feet.

Corner lies at intersection of North and East-West old blazed lines, about 350 feet West of wood USFS section line crossing marker on 12-inch diameter Fir, alongside road.

September 10, 1975

B. Malotte

R. Frost

Approved by: Edward McGinty

County Surveyor

### NOTE:

See C.S. field notes book #3 (1975) page 207 & project file 75-18. R.F.

See Job File 80-8 R.F.

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 240300

Quarter corner common to Sections 20 and 29 of Township 32 South, Range 1 West, W.M.

Found at corner position exposed 10 inches in a mound of stones the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass disc set on First Re-establishment in 1975 and marked:

JACKSON COUNTY 1975  
T32S R1W  
20  
¼S —  
29

Single remaining original bearing tree recorded by R. Moore of the GLO in 1883, the remains of a fir stump found and measured to center bears Record: N 28° W, 9.9 feet.

Bearing trees recorded on First Re-establishment found with healed double blazes and measured to center at lower blaze:

- White fir now 15-inch diameter bears Record: N 4½° E, 33.9 feet.
- White fir now 14-inch diameter bears Record: N 45° W, 35.0 feet

Marked the new bearing tree "CS" "BT" and took measurements to center at lower blaze;

- White fir 15-inch diameter bears S 84° W, 9.1 feet.
- (Road intersection to the southeast of corner; no trees available.)

Corner lies approximately 25 feet west of "Y" in road and approximately 650 feet southerly of BLM gate.

April 17, 2007

B. Beeman

H. Durkee

Roger R. Roberts

Jackson County Surveyor

P. - 94

V. - 14°25'