

FIRST RE-ESTABLISHMENT

GCDB 300300

Sections corner common to Sections 20, 21, 28 and 29, Township 32 South, Range 1 west, W.M.

Found at the corner position, exposed 6 inches and in a mound of stones, the 2½-inch diameter galvanized iron pipe with a 3½-inch diameter brass cap set by the BLM in 1966, marked:

T32S R1W	
S20	S21
1966	
S29	S28

Single remaining original bearing tree recorded by R. Moore of the GLO in 1883, a large fir, dead and down bears Record: N 40° E, 18.5 feet to approximately center of stump hole.

Bearing trees recorded by the BLM in 1966 found with healed single blazes and measured to center of trees at base:

- Douglas Fir now 22-inch diameter bears Record: N 52° E, 26.4 feet.
- White fir now 18-inch diameter bears Record: S 15° E, 48.2 feet.
- Douglas Fir now 21-inch diameter bears S 75° W, 6.6 feet. Record: 5.9 feet.
- White fir snag bears Record: N 13° W, 8.6 feet.

Mark new bearing tree "CS" "BT" and took measurements to center of tree at lower blaze:

- White fir 12-inch diameter bears N 59° W, 8.4 feet.

Corner lies approximately 50 feet westerly from graveled road.

April 17, 2007

H. Durkee

B. Beeman

Roger R. Roberts

Jackson County Surveyor

P. - 95

V. - 14°25'