

## FIRST RE-ESTABLISHMENT

GCDB 340200

Quarter corner common to Section 28 and 33, Township 32 South, Range 1 West, W.M.  $V = 20^\circ$

Found, projecting 2 inches, the original (undisturbed) 17x10x10-inch (43x25x25 cm), stone.  
Record: 18x12x8 inches (45x30x20 cm.) marked: "¼" on North face as recorded by R. Moore in 1883.

I replaced said stone with a 1x36-inch (2.5x91 cm) galvanized iron pipe set 30 inches (76 cm) in the ground with a 2½-inch (6 cm.) bronze disc marked:

Jackson County 1977  
T32S R1W  
28  
¼S —  
33

The single remaining original bearing tree, a Douglas fir, now 27-inch (69 cm.) diameter, bark scribed "BT" bears South, 41.00 feet (12.50 m) to center of tree. Record: South, 40.92 feet (12.47 m).

I mounded stones around corner, deposited original stone alongside as a memorial, marked new trees "C.S. BT," and took measurements to center of trees at lower blaze:

- Douglas fir, 8-inch (20 cm) diameter bears N85°E, 12.10 feet (3.69 m).
- Incense cedar, 8-inch (20 cm.) diameter bears S1½°W, 25.65 feet (7.82 m).

Corner lies 30 feet (9 m.) East of stream channel C. South.

January 27, 1977

B. Malotte

R. Frost

Approved by: Edward McGinty  
County Surveyor