

FIRST RE-ESTABLISHMENT

GCDB 340300

Quarter corner common to Section 21 and 28, Township 32 South, Range 1 West, W.M. $V = 20\frac{1}{2}^\circ$

Found, the single remaining bearing tree recorded by R. Moore in 1883, a Douglas fir, now 19-inch (48 cm.) diameter, containing scribed "4" in partly exposed face.

From the preceding evidence:

- I set a 1x36-inch (2.5x91 cm) Galvanized iron pipe, 32 inches (81 cm) in the ground with a 2½-inch (6 cm) bronze disc marked:

Jackson County 1977
T32S R1W
21
¼S —
28

From which, the above-described original BT bears Record: $N55^\circ W$, 13.20 feet (4.02 m) to scribed face.

Original stone not found. I mounded stones around corner, marked the following trees "C.S. BT," and took measurements to center of trees at lower blaze:

- White fir, 5-inch (13 cm) diameter bears $N26^\circ E$, 23.08 feet. (7.03 m)
- Douglas fir, 11-inch (28 cm) diameter bears $S14^\circ W$, 63.63 feet. (19.39m)

Corner lies on steep (60%) N.W. slope, 32 feet (10 m) North of ridge top c. $N82^\circ W$ and an estimated 200 feet (61m.) South of draw c. E-W.

January 27, 1977

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor