

**FIRST RE-ESTABLISHMENT**

**GCDB 540400**

Quarter corner common to Sections 14 and 23, Township 32 South, Range 1 West, W.M.

Found at the corner, projecting 9 inches, the 1-inch diameter galvanized iron pipe set on Survey No. 5336, dated 1973.

In top of said iron pipe set a 2½-inch diameter bronze cap marked:

JACKSON COUNTY 1981  
T32S R1W  
14  
¼S —  
23

From which the original bearing trees marked by Rufus Moore in 1883 found and measurements taken to center of trees at lower blaze:

- Douglas Fir, 16-inch diameter with healed blazes bears N72°W, 2.8 feet. Record: 2.64 feet.
- Douglas Fir, 30-inch diameter with axed opened upper face containing scribed "4s" bears S33°E, 16.34 feet. Record: 15.84 feet.

Bearing tree recorded on Survey No. 5336, a Douglas Fir, now 26-inch diameter with healed blazes bears N40°E, 9.80 feet to center of tree at lower blaze. Record: N36¼°E, 8.8 feet to face.

Corner lies on Southwest slope about 370 feet East of draw c. S30°W and about N45°E, 600 feet from location marker on 2 inches fir alongside road.

June 24, 1981  
R. Frost  
R. Templin

Edward McGinty  
County Surveyor

V = 21½°  
P. -99