


FIRST RE-ESTABLISHMENT

GCDB 600100

Section corner common to Sections 35 and 36, Township 32 South, Range 1 West and Sections 1 and 2, Township 33 South, Range 1 West, W.M.

Found at the corner, projecting 15 inches, the 2-inch diameter iron pipe with standard 2½-inch diameter GLO brass cap marked:



Original bearing trees marked by N. Ford in 1855 and noted in 1917 GLO record, found as follows:

- Shasta Red Fir, 20-inch diameter, with healed blazes bears Record: (1917); N43°E, 9.90 feet to center.
- Tipped over hemlock, about 45-inch diameter, containing scribed "T" in partially exposed lower face bears S80°E, 30.0 feet to base. Record (1917): S60°E, 25.08 feet.

The single remaining bearing tree marked by GLO in 1917 found:

- Hemlock stump, 16-inch diameter, scribed "33R1" in rotted face bears S68°W, 7.92 feet to center. Record: S62°W, 7.92 feet.

SEE ALSO Survey No. 2632, dated 1964.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Hemlock, 7-inch diameter bears S44°E, 61.05 feet (18.60 m).
- Yew, 12-inch diameter bears S2½°E, 25.50 feet (7.77 m).
- Douglas Fir, 6-inch diameter bears N59°W, 14.35 feet (4.37 m).

Corner lies about 120 feet South of location marker on 30-inch diameter Fir stump alongside West Branch Road.

January 20, 1982

R. Frost

R. Templin

Witness: T. Newcomb - USFS

Edward McGinty

County Surveyor

V = 21°


P. -9

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT
GCDB 600100**

Section corner common to Sections 35 and 36, Township 32 South and Sections 1 and 2, Township 33 South, Range 1 West, W.M.

Found at the corner position, exposed 16 ins., the 2 ins. diam. galv. iron pipe with a 2½ ins. diam. brass cap set by the GLO in 1917, marked:



Original bearing trees recorded by N. Ford of the GLO in 1850, found and measured to center at base:

- R. Fir, now 23 ins. diam. with healed blazes, brs. record; N 43° E, 9.9 ft.
- Large Hemlock, dead down and rotted, brs. record; S 80° E, 30.0 ft.

Bearing trees recorded on 1st Re-establishment in 1982, found with healed double blazes and measured to center at lower blaze:

- Hemlock, now 10 ins. diam. brs. record; S 44° E, 61.1 ft.
- D. Fir, now 16 ins. diam. brs. record; N 59° W, 14.4 ft.
- Yew, now 14 ins. diam. with scribe marks "CS" "BT" in partially healed double blazes, brs. record; S 2½° E, 25.5 ft.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- D. Fir 10 ins. diam., brs. S 41° W, 13.7 ft.

Corner lies approx. 120 ft. west of west branch of Elk Creek Road.

June 19, 2012
H. Durkee

Kerry Bradshaw
Jackson County Surveyor

P. – 204
V. – 18°15'