

**PROPORTIONED CORNER**

**GCDB 600340**

Quarter corner to Sections 23 and 24, Township 32 South, Range 1 West.

Found no evidence of the original corner.

At a point midway and on line between the Northwest and Southwest corners of Section 24, set a 1" x 36" galvanized iron pipe with top 2" above ground surface for corner.

From which:

- A 10" Fir, scribed "CS-BT" bears N. 74°E., 5.9 feet;
- A 13" Fir, scribed "CS-BT" bears S. 34°W., 18.0 feet.

August 25, 1955  
Mark E. Boyden  
L. D. Bernstson

**ALSO SEE RECORDED SURVEY NO. 4663.**

**PROPORTIONED CORNER - NO FIRST RE-ESTABLISHMENT**

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

SPECIAL CORNER

SECOND RE-ESTABLISHMENT

GCDB 600340

Quarter corner common to Sections 23 and 24, Township 32 South, Range 1 West, W.M.

Found at the corner position, protruding 2 inches and in a mound of stones, the 1-inch diameter galvanized iron pipe, set by single proportion on First Re-establishment\* in 1955.

Set in top of said pipe and in cement, a 2½-inch diameter brass cap, marked:

JACKSON COUNTY SURVEYOR  
T32S R1W  
¼ S23 • S24  
2003

Single remaining bearing tree recorded on First Re-establishment in 1955, a d. fir, now 19-inch diameter with healed blazes and scorched but healthy bears S 34°W, 18.3 feet to center of tree at lower blaze. Record: 18.0 feet to face.

Bearing tree recorded on Survey No. 4663, a d. fir, now 16-inch diameter and high-stumped with scribe marks "¼ S2" on opened upper face bears N 69½° E, 27.4 feet to center. Record: 26.7 feet to face.

Take new references:

- 5/8 x 24-inch rebar with 1½-inch diameter aluminum caps, protruding 2 inches and marked:



- ▶ Bears S 15½° E, 19.9 feet.
- ▶ N 70½° E, 25.9 feet (set at base of Survey No. 4663 BT)
- Mag nail in center of sawed cedar stump 40-inch diameter bears N 43° E, 16.55 feet.

Corner lies approximately 50 feet easterly of end of Spur Road

December 22, 2003

H. Durkee

Roger R. Roberts  
Jackson County Surveyor

P. -178

V. -15°40'

\*NOTE: First re-establishment refers to establishment of Proportioned Corner in 1955. (6/8/2016)