

FIRST RE-ESTABLISHMENT

GCDB 600400

Section corner common to Sections 13, 14, 23 and 24, Township 32 South, Range 1 West, W.M.
 $V = 11\frac{1}{2}^\circ$

Found, projecting 10-inch (25 cm) in mound of stone, a 1-inch (2.5 cm) diameter iron pipe with 2½-inch (6.4 cm) diameter pot metal filled ex-pander marked:

T32S R1W	
S14	S13
S23	S24
1967	

Original bearing trees recorded by R. Moore in 1883, found as follows:

- Hollow and rotted fir snag, 37-inch (94 cm) diameter bears Record: N38°E, 17.16 feet (5.23 m) to estimated face. Re-measured 18.20 feet (5.55 m) to center of tree.
- Fir stob, 36-inch (91 cm) diameter scribed "BT" in exposed lower face bears S66°E, 12.33 feet (3.76 m) to scribed face. Record: S66°E, 12.54 feet (3.82 m).
- Fir, 27-inch (69 cm) diameter, with healed blazes bears Record: S10°W, 15.18 feet (4.63 m) to estimated face. Re-measured 16.01 feet (4.88 m) to center of tree.
- Fir, 35-inch (89 cm) diameter, with scribe marks visible in partially exposed upper face bears Record: N56°W, 15.84 feet (4.83 m), on slope, to estimated lower face. Re-measured 16.28 feet (4.96 m) to center of tree.

I marked new trees "CS BT" and took measurements to center of trees at lower blaze:

- Douglas Fir, 5-inch (13 cm) diameter bears N14°E, 29.93 feet (9.12 m).
- Douglas Fir, 10-inch (25 cm) diameter bears S85°E, 48.85 feet (14.89m).

Corner lies on East (50%) slope, an estimated 550 feet (167.64 m) south of location marker on 30-inch (76 cm) diameter Fir, located about 100 feet (30.48 m) East of the junction of "L" and "E" logging roads.

August 8, 1979

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor