

FIRST RE-ESTABLISHMENT

GCDB 640300

Quarter corner to Sections 24 and 25, Township 32 South, Range 1 West.

- Found the 8" x 8" x 22" basalt stone with "¼" chiseled on one face;
- The 22" Fir with scribe legible for the Northeast BT
- The snag of the Southwest BT with scribe visible.
- Chiseled an "X" on top of said stone and set same 12" in the ground for corner.

From which:

- The 22" Fir (original BT) bears N. 27° E., 23.1 feet;
- A 10" Fir, scribed "CS-BT" bears S. 10° E., 65.8 feet;
- A 16" Fir, scribed "CS-BT" bears N. 54½° W., 45.3 feet.

June 24, 1955
Mark E. Boyden
L. D. Bernstson
O.E. Hendrickson

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 640300

Quarter corner common to Sections 24 and 25, Township 32 South, Range 1 West, W.M.

Found projecting 6 inches, the 22x9x8-inch stone with an "x" chiseled into the top, as described on First Re-establishment, page 3, in 1955.

Replaced said stone with, and deposited alongside of, a 1x36-inch galvanized iron pipe set 32 inches in the ground.

In the top of said pipe, set in concrete, a 2½-inch diameter brass cap marked:

T32S R1W
24
¼S —
25
C.S.
1988

Original bearing tree marked by Rufus S. Moore in 1883 found:

- Douglas Fir, now 31-inch diameter with scribed "4S" and "BT" visible bears Record: N27°E, 23.25 feet to face. Record distance: 23.10 feet. Re-measured 24.3 feet to center of tree at root crown.

Bearing trees marked on First Re-establishment found with double healed blazes and measured to center of trees at lower blaze:

- Fir snag, now 17-inch diameter bears Record: S10°E, 66.25 feet. Record distance; 65.8 feet to face.
- Douglas Fir, now 21-inch diameter bears N53¾°W, 46.0 feet. Record: N54½°W, 45.3 feet to face.

Scribe a new tree "CS-BT":

- Douglas Fir, 14-inch diameter bears S14½°W, 15.95 feet to center of tree at lower blaze.

Corner lies in timber on a 35% southwesterly slope.

March 30, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18¾°
P. -115