

FIRST RE-ESTABLISHMENT

GCDB 640400

Quarter corner to Sections 13 and 24, Township 32 South, Range 1 West.

- Found a 14x9x?-inch basalt stone firmly set with "¼" chiseled on the North face.
- Also found a Fir stump to the Southeast with scribe visible and stump hole for the Northwest BT.
- Chiseled an "X" on said stone for corner.

From which:

- A 6" Fir, scribed "CS-BT" bears N85°W, 14.0 feet.
- A 4" Fir, scribed "CS-BT" bears N13°W, 10.3 feet.

Found an 8" Fir, recently scribed "¼" which bears N82°E, 9.2 feet.

June 27, 1955
Mark E. Boyden
L. D. Bernstson
O. E. Hendrickson

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 640400

Quarter corner common to Sections 13 and 24, Township 32 South, Range 1 West, W.M.

Found at the corner projecting 9 inches, the original 18x16x8-inch stone with "x" in top, set by Rufus Moore in 1883.

Replaced said stone with and deposited it alongside a galvanized iron pipe, 1-inch diameter, 36 inches long, 24 inches in ground with 2½-inch diameter bronze cap marked:

JACKSON COUNTY 1981

T32S R1W

13

¼S —

24

From which bearing trees recorded on First Re-establishment, page 3, dated 1955, found and took measurements to center of trees at lower blaze:

- Douglas Fir, 16-inch diameter with healed single blaze bears N82°E, 9.50 feet. Record: 9.20 feet.
- Douglas Fir, 13-inch diameter with healed blazes bears N85°W, 14.60 feet. Record: 14.0 feet.
- Douglas Fir, 12-inch diameter with healed blazes bears N13°W, 10.37 feet. Record: 10.3 feet.

Corner lies on East slope, 100 feet West of bottom of draw and approximately 400 feet, S49°E from location marker on sawed stump located at the top of North slope at end of logging road.

June 25, 1981

R. Frost

R. Templin

Edward McGinty

County Surveyor

P. -100