

PROPORTIONED CORNER

GCDB 700600

Section corner on the Willamette Meridian 1, 6, 12 and 7. Sections 1 and 12, Township 32 S. Range 1 West and Sections 6 & 7 Township 32 S. Range 1 East.

No definite evidence of the original corner or BTs. Ran random line between the first $\frac{1}{4}$ corner to the north and the first $\frac{1}{4}$ corner to the south, at which corners had good evidence of the original corners.

For the said section corner set an 8"x10"x22" basalt stone on single proportion distance.

From which:

- A 26" fir scribed CS-BT bears north $81\frac{1}{2}^{\circ}$ west, 22 feet,
- Scribe a 6" live oak CS-BT which bears south 52° West 18.5 feet,
- Scribe a 5" live oak CS-BT which bears south $22\frac{1}{4}^{\circ}$ east 23.0 feet,
- Scribe a 6" live oak CS-BT which bears north 75° east 22.0 feet.

Found a $1\frac{1}{4}$ " squared fir stake marked with chalk, W.M. line, approximate corners 1 & 12, 2497 feet north of $\frac{1}{4}$ corner Section 12, 5 chains south to ravine, intersect blaze line. Noted possible remains of 4 BTs.

Which stake bears south 41° east 47.5 feet along see Survey No. 534.

June 26, 1953
C. Z. Boyden
L. D. Pinkham
M. E. Boyden