

FIRST RE-ESTABLISHMENT

GCDB 100240

Quarter corner common to Section 25, Township 32 South, Range 3 East and Section 30 Township 32 South, Range 4 East, W.M.

Found at the corner position, exposed 7 inches and in a mound of stones, the 2½-inch diameter galvanized iron pipe with a 3½-inch diameter brass cap set by the BLM in 1962, marked:

T32S
R3E | R4E
S25 | S30
1962

Single remaining original bearing tree recorded by Rufus Moore of the GLO in 1884,

- A Douglas Fir, now 42-inch diameter with healed blazes bears S 82° E, 5.1 feet to center at base. Record: 4.6 feet to face.

Bearing trees recorded by the BLM in 1962, found with healed single blazes and measured to center of trees at base:

- Douglas Fir, now 13-inch diameter bears Record: S 16° E, 13.2 feet.
- White Fir, now 20-inch diameter bears Record: S 73° W, 20.1 feet.

Marked new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- White Fir 9-inch diameter bears N 47½° W, 22.5 feet.

Corner lays approximately 600 feet north "K" tag on large Douglas Fir at beginning of blocked spur road.

September 6, 2007

H. Durkee
B. Beeman

Roger R. Roberts
Jackson County Surveyor

P. - 209
V. - 15°45'