

FIRST RE-ESTABLISHMENT

GCDB 200100

Section corner common to Sections 31 & 32, Township 32 South, Range 4 East, and Sections 5 & 6, Township 33 South, Range 4 East, W.M. V=21

Found, firmly set, the original 14x8x8-inch stone, marked with 5 notches on the East & 1 on the West side as recorded by R. Moore in 1884.

I replace said stone, with a 1x36-inch G.I. pipe set 30 ins. in the ground with a 2½ ins. bronze disc marked:

Jackson County 1976	
T32SR4E	
31	32

6	5
T33S	

Original bearing trees found as follows:

- Douglas Fir, 43-inch diameter, containing bark scribe marks including "T" & "S" in burned upper bark face bears Record: N 50° E, 12.54 feet to estimated original position of scribing. Re-measured 13.79 feet to center of tree.
- Douglas Fir, 44-inch diameter, with bark scribed "T32SR4" & partial "B" bears Record: N32°W, 22.44 feet to estimated original position of scribing. Re-measured; 23.69 feet to center of tree.
- I re-scribed the above original trees "CS BT" in single (low) blaze.
- The SE & SW BTs are now gone.

I deposited original stone alongside corner as a memorial, marked new trees CS BT, & took measurements to center of trees at lower blaze:

- White Fir, 9-inch diameter bears S 67° E, 108.77 feet.
- Red Fir, 24-inch diameter bears S 87° W, 22.25 feet.

Corner lies on north slope about 150 feet S 9° W of location marker on 32 inches Fir located on north edge of road.

November 17, 1976
R. Frost
B. Malotte

Approved by: Edward McGinty
County Surveyor