

## FIRST RE-ESTABLISHMENT

GCDB 200140

Quarter corner common to Section 31 and 32, Township 32 South, Range 4 East, W.M.  $V = 22\frac{1}{2}^\circ$

Found the original 20x16x10-inch stone (tipped over) marked "¼" as recorded by R. Moore in 1884.

I replaced said stone with a 1x36-inch Galvanized iron pipe, set 24 inches in the ground with a 2½-inch bronze disc marked:

JACKSON COUNTY 1975

T32S R4E

¼S

31 | 32

Original BTs found as follows:

- Douglas Fir, 12-inch diameter, scribed "BT" bears record, N53°E, 5.94 feet to scribed face.
- The base and stump remains of a down and rotted Fir of undetermined diameter bears Record: S60°W, 11.88 feet.

I mounded stones around corner, deposited original stone alongside as a memorial, marked new trees C.S. BT, and took measurements to center of trees at lower blaze:

- Yew, 8-inch diameter bears N39½°E, 25.68 feet.
- White Fir, 15-inch diameter bears N50½°W, 53.32 feet.

Corner lies about 600 feet North of wood line crossing marker on post near road junction.

October 29, 1975

R. Frost

T. Newcomb, USFS

Approved by: Edward McGinty  
County Surveyor