

**FIRST RE-ESTABLISHMENT
QUARTER CORNER TO SECTION 5 ONLY
GCDB 240700**

North quarter corner to Section 5 only, Township 32 South, Range 4 East, W.M. $V = 22\frac{1}{4}^\circ$

From the following evidence, at the location described below, I set a 1x36-inch (2.5x91 cm) Galvanized iron pipe 30 inches (76 cm) in the ground with a 2½-inch (6 cm) bronze disc marked:

Jackson County 1977
T31S
¼S —
5
T32S R4E

Original bearing trees marked by R. Moore in 1884 and recorded on 1937 retracement, by Price and Carter found as follows:

- White Pine, sawed stump, 36-inch (91 cm) diameter bears (1937) Record: N34°E, 11.88 feet (3.62 m) to center.
- Fir stob, 32-inch (81 cm) diameter bears (1937) Record: S56°W, 16.50 feet (5.03 m) to center.

Bearing trees marked in 1937 by Price and Carter:

- Hemlock, 18-inch (46 cm) diameter, (recorded as fir) with healed blaze bears Record: S40°E, 29.70 feet (9.05 m), on slope, to center. Re-measured: 28.6 feet (8.72 m) to center of tree.
- Shasta red fir, 15-inch (38 cm) diameter, with scribed "T" visible in partly exposed face bears S34°W, 24.42 feet (7.44 m) to center. Record: S35°W, 24.42 feet (7.44 m).

Original stone and 1937 pipe and brass cap not found.

Corner lies in old skid trail about 180 feet (55 m) west of draw c. N60°W.

October 5, 1977

B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor