

FIRST RE-ESTABLISHMENT

GCDB 300300

Section corner common to Sections 20, 21, 28, & 29, Township 32 South, Range 4 East.

Found stone at corner but could not find any grooves on same;

- The S.W. BT, a 7" Yew, was dead but still standing with scribing legible;
- Also found the stump hole to the S.E. and the stump to the N.E. all of which agree with the locations of the stone for the corner.

Set a 2"x36" iron pipe 33" in the ground for corner to replace said stone, from which:

- A 6" Fir, scribed "CS-BT" bears N. 65° W. 20.2 feet;
- A 7" Chinquapin, scribed "CS-BT" bears N. 42° E. 14.2 feet.;
- A 5" Yew, scribed "CS-BT" on one blaze bears S. 60° E. 22.2 feet.
- A 30" Cedar, scribed "CS-BT" bears S. 16° W. 31.3 feet;

July 10, 1950
C. Z. Boyden
L. D. Pinkham
M. E. Boyden

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT


SECOND RE-ESTABLISHMENT

GCDB 300300

Section corner common to Sections 20, 21, 28, 29, Township 32 South, Range 4 East, W.M.

Found projecting 4 inches, the 2-inch diameter galvanized iron pipe set on First Re-establishment in 1950.

From the top of which, is found a 1-inch diameter galvanized iron pipe projecting 4 inches with a 2½-inch (outside diameter), pot metal filled pipe reducer, marked:



Directly over the lower (c.s.) pipe.

Bearing trees marked in 1950 found:

- Chinquapin, 12-inch diameter, with healed blazes bears N42°E, 14.2 feet, to center at lower blaze.
- Yew, 7-inch diameter, containing scribed (partial) "B" on single blaze bears S60°E, 22.2 feet to center at base. Added upper blaze and scribed same "C.S."
- Cedar, 33-inch diameter, with partly healed blazes bears S16°W, 32.0 feet to center at lower blaze. Basis of bearing.
- White fir, 16-inch diameter, with healed blazes bears N65°W, 20.4 feet to center at lower blaze.
- A down and burnt yew, 7-inch diameter containing scribe marks, including "32S R4E" bears S60°W, 10 feet to base. (Orig. BT)
- A 12x8x8-inch stone is found (loose) alongside the corner. No marks are discernible.

Corner lies at the Northeast corner of clear-cut.

October 7, 1996
R. Frost, Tech.
T. Newcomb, Tech.

Roger Roberts
County Surveyor

P. -48