

FIRST RE-ESTABLISHMENT

GCDB 300440

Quarter corner common to Sections 16 and 17, Township 32 South, Range 4 East, W.M. $V = 21^\circ$

Found firmly set, the original 12x11x7-inch (record 10x10x10-inch) stone marked "¼" on West face as recorded by R. Moore in 1884.

I replaced said stone with a 1x36-inch Galvanized iron pipe set 32 inches in the ground with a 2½-inch bronze disc marked:

JACKSON COUNTY 1978
T32S R4E
17 | 16
¼S

Original bearing trees found as follows:

- Sugar pine snag, 52-inch diameter marked "¼S" in exposed upper face, bears $S35^\circ E$, 37.1 feet to scribed face. Record: $S35^\circ E$, 36.30 feet
- Cedar, 27-inch diameter bears $S30^\circ W$, 38.47 feet to center. Record: $S30^\circ W$, 36.30 feet.

I deposited original stone alongside corner, marked new trees CS BT, and took measurements to center of trees at lower blaze:

- Douglas fir, 17-inch diameter bears $N61^\circ E$, 8.70 feet.
- Sugar pine, 21-inch diameter bears $S87^\circ W$, 16.50 feet.

Corner lies 460 feet South of ridge, C. $N70^\circ E$ and about 100 feet South of location marker on 19-inch diameter fir alongside road. c. $N50^\circ E$.

October 19, 1978

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor