

FIRST RE-ESTABLISHMENT
QUARTER CORNER TO SECTION 4 ONLY
GCDB 340700

North quarter corner of Section 4, Township 32 South, Range 4 East. W.M. $V = 20^\circ$

Found projecting 7 inches (18 cm) the 1-inch (2.5 cm) diameter iron pipe with GLO brass cap marked:

¼ —
S4
1937

Set by Price & Carter in 1937.

Original bearing trees recorded by R. Moore in 1884 and noted by Price and Carter on 1937 dependent resurvey found as follows:

- White Pine, 17-inch (43 cm) diameter, containing scribe marks in partially exposed face bears $S47^\circ W$, 10.77 feet (3.28 m) to center. Record 1937: $S47^\circ W$, 10.56 feet (3.22 m).
- Shasta Red Fir snag, 18-inch (46 cm) diameter bears $N24^\circ W$, 8.43 feet (2.57 m) to center. Record 1937: $N24^\circ W$, 8.58 feet (2.62 m).
- **Note:** marks on this tree were obliterated per Price and Carter's record. However, the blazes do not now appear to have ever been opened.
- BT marked by Price and Carter: now a sawed fir stump 38-inch (97 cm) diameter bears $S37^\circ E$, 66.95 feet (20.41 m) to center. Record: $S37^\circ E$, 68.64 feet (20.92 m).
- The original stone found deposited alongside (west) corner as noted by Price and Carter.

I marked a new tree CS-BT:

- Shasta red fir, 18-inch (46 cm) diameter bears $S84^\circ E$, 85.35 feet (26.01 m) to center of tree at lower blaze.

Corner lies in clear-cut unit, 25 ft (8 m) south of logging road.

November 7, 1977

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT
QUARTER CORNER TO SECTION 4 ONLY
GCDB 340700**

North quarter corner of Section 4 only of Township 32 South, Range 4 East, W.M.

Found at the corner position the 1-inch diameter galvanized iron pipe with the 2½-inch diameter brass cap exposed 8 inches set by Price and Carter of the GLO in 1937 and marked:

—————
¼ S4
1937

Original bearing trees recorded by R. Moore of the GLO in 1884 found and measured to center at base:

- White pine with spiked top now 21-inch diameter bears Record: S 47° W, 10.8 feet.
- Red fir rotted stump bears Record: N 24° W, 8.6 feet.

Bearing tree recorded by Price and Carter of the GLO in 1937 found and measured to center of base:

- Fir rotted remains of sawed stump bears Record: S 37° E, 67.0 feet.

Marked new bearing trees with "CS" and "BT" and measured to center at lower blaze:

- S. Red Fir 9-inch diameter bears S 31½° W, 25.4 feet.
- S. Red Fir 11-inch diameter bears S 10½° E, 40.3 feet.

Corner lies approximately 20 feet south of old logging spur road.

October 12, 2006

B. Beeman
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 180
V - 16°20'