

FIRST RE-ESTABLISHMENT

GCDB 400200

Section corner common to Sections 27, 28, 33 and 34, Township 32 South, Range 4 East, W.M.
 $V = 23^\circ$

Found 12x12x12-inch stone firmly set with 1 notch on South and 3 notches on East edges as recorded by R. S. Moore in 1884:

I replaced with a 2½x30-inch Galvanized iron pipe projecting 15 inches with flanged end and 2½-inch diameter brass cap marked:

T32S R4E	
S28	S27
S33	S34
C.S. 1979	

From which I found the following original bearing trees:

- Black Oak, 15-inch diameter with "S" and partial "2" scribed visible in open upper face. Bears $N17^\circ E$, 9.24 feet to face. Record: $N15^\circ E$, 9.24 feet.
- Black Oak, 14-inch diameter with healed blazes bears $N85^\circ W$, 35.1 feet to center of tree at lower blaze. Record: $N85^\circ W$, 36.96 feet

I marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir, 11-inch diameter bears $N39^\circ E$, 85.08 feet.
- White Fir, 8-inch diameter bears $S38\frac{3}{4}^\circ E$, 42.8 feet.
- White Fir, 12-inch diameter bears $S40^\circ W$, 31.9 feet.

I placed found stone alongside corner and raise mound of stone around corner.

Corner lies on East end of rock out-crop and about 1100 feet East of location marker on White Fir, 18-inch diameter

I placed monument marker sign $N20^\circ W$, 6½ feet from corner.

November 16, 1979

B. Malotte

Witness: C. Davidson

J. Gallegos

H. Center

Approved by: Edward McGinty

County Surveyor