


**FIRST RE-ESTABLISHMENT
 CORNER COMMON TO SECTIONS 1 AND 2 ONLY
 GCDB 600700**

Section corner common to Sections 1 and 2 only, on the North township line of Township 32 South, Range 4 East. W.M.

At the corner, found projecting 18 inches in mound of stone, the 2-inch diameter iron pipe, with 2½-inch diameter standard GLO brass cap marked:



As recorded by Price and Carter on 1937 dependent resurvey.

Bearing trees marked by R. Moore in 1884 and recorded in 1937 found:

- The base of a down (tipped over) Red Fir, 24-inch diameter, with healed blazes bears Record (1937): S9°E, 26.40 feet.
- Red Fir, 21-inch diameter, with healed blazes bears S74°W, 20.46 feet to center.

Marked a new tree "CS" "BT":

- Red Fir, 27-inch diameter bears S11°W, 20.35 feet to center of tree at lower blaze.
- **Note:** No suitable tree available in SE quadrant.

Corner lies about 100 feet West of location marker on 7-inch diameter hemlock, alongside road, on top of small rock point about 50 feet West and 30 feet above same road.

August 4, 1982	Edward McGinty	V = 21°
R. Frost	County Surveyor	
R. Templin		P. -111

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 1 AND 2 ONLY
GCDB 600700**

Section corner common to Sections 1 and 2 only, Township 32 South, Range 4 East, W.M.

Found at the corner position, exposed 18 inches and in a large mound of stones, the 2-inch diameter galvanized iron pipe with a 2½-inch diameter Brass cap set by Price and Carter of the GLO in 1937, marked:

T31S R4E
S35
S2 | S1
T32S R4E
1937

Original bearing trees recorded by R. Moore of the GLO in 1884 found with healed blazes and measured to center of trees at base:

- Red Fir, dead and down bears Record: S9°E, 26.4 feet.
- Red Fir, now 21-inch diameter bears Record: S74°W, 20.5 feet.

Bearing tree recorded on First Re-establishment in 1982, a Red Fir snag with healed double blazes bears S 11° W, 20.9 feet. Record: 20.4 feet.

Marked new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Hemlock, 7-inch diameter bears S 20° W, 34.1 feet.
- No suitable trees available in southeast quadrant.

Corner lies atop a rock outcrop, approximately 20 feet southerly and 30 feet above a gravel road.

October 24, 2006

H. Durkee
B. Beeman

Roger R. Roberts
Jackson County Surveyor

P. - 190
V. - 16°