

FIRST RE-ESTABLISHMENT

GCDB 700100

Township corner common to Townships 32 and 33 South, Ranges 4 and 5 East of the Willamette Meridian, on the Jackson-Klamath County line.

Found at the corner, firmly set, the original 24x16x12-inch stone set by R. Moore in 1884, marked with 6 notches on each edge.

Replaced said stone with and deposited it alongside, a 1x36-inch Galvanized iron pipe, set 30 inches in the ground, in a small mound of stones.

In the top of said pipe, set in concrete, a 2½-inch diameter brass cap marked:

T32S	
R4E	R5E
36	31

1	6
C.S.	
T33S	
1986	

References recorded by R. Moore found:

- A mound of stone, 3x3x1½ feet high bears West, 5.0 feet.
- A Red Fir, now 32-inch diameter, with no discernable marks bears N30°W, 115.1 feet to center of tree near base. Record: 113.52 feet.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Red Fir, 12-inch diameter bears N53¼°E, 38.1 feet.
- White Fir, 10-inch diameter bears S51¾°E, 14.15 feet.
- Red Fir, 16-inch diameter bears S28½°W, 31.40 feet.

Corner lies on 19% southwesterly slope, approximately 100 feet north-easterly from a slope break to a 50% southwesterly slope, approximately 100 feet N60°W from the northwesterly edge of a small brush patch and an estimated 1000 feet easterly from the easterly edge of a large brush patch.

August 18, 1986
D. Edwards
R. Frost

Edward McGinty
County Surveyor

V = 19¼°
P. -222