


FIRST RE-ESTABLISHMENT

GCDB 700200

Section Corner common to Sections 25 and 36, Township 32 South Range 4 East, W.M.

Found stone 14x14x8-inch protruding 7 inches aboveground with 5 notches on the North face and 1 notch on the South face, set by Rufus Moore in 1884.

Removed stone and set a 1x30-inch Galvanized iron pipe 12 inches in the ground to bedrock with attached Jackson County Surveyor 2½-inch diameter brass cap marked:



Protruding 2 inches above large mound of stone with original stone alongside.

Original bearing tree marked by Moore found:

- Pine snag 24-inch diameter with scribe marks visible on partially healed pitched over face bears Record: N33°W, 35.64 to face. Re-measure 36.64 to center of snag at base.

Marked new trees 'CS BT' and measured to the center of tree at base.

- Red Fir 19-inch diameter bears N24°E, 41.97 feet.
- Hemlock 7-inch diameter bears S34°E, 25.45 feet.
- Hemlock 13-inch diameter bears S15½°W, 43.75 feet.
- White Pine, with dead top, 12-inch diameter bears N72°W, 59.94 feet.

Corner lies on a bench, 40 feet South of grade break.

October 22, 1997

S. Beecher

T. Newcomb

V = 18°

P. -91