

FIRST RE-ESTABLISHMENT

GCDB 700340

The East quarter corner of Section 24, Township 32 South, Range 4 East, W.M. on the Jackson-Klamath County line.

Found firmly set, the original 14x10x7-inch stone marked "¼" on the West side, by R. Moore in 1884. Replaced said stone with, and deposited it alongside, a 1x36-inch Galvanized iron pipe, set 29 inches in the ground.

In the top of said pipe, set in concrete, a 2½-inch diameter brass cap marked:

T32S
R4E R5E
¼s |
24 |
C.S.
1986

The single remaining original bearing tree,

- A Red Fir snag, now 32-inch diameter containing scribe marks including "B" and an inverted T" in opened lower face bears Record: S35°E, 3.96 feet to said face.

The original Southwest bearing tree is now gone.

Mounded stones around corner, marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- A Hemlock, 11-inch diameter bears S42°W, 18.25 feet.
- A Hemlock, 14-inch diameter bears N59°W, 28.40 feet.

Corner lies on a 10% Northwesterly slope, approximately 35 feet South of the top of a 40% northerly slope and approximately 300 feet North of a location marker on a 7-inch diameter bent over Red Fir, which lies on the North edge of a large clearing.

September 2, 1986
D. Edwards
R. Frost

Edward McGinty
County Surveyor

V = 19°
P. -236