

FIRST RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 36 ONLY  
GCDB 700140

East quarter corner common to Section 36 only, Township 32 South, Range 4 West, W.M.

Found firmly set, the original 17x16x4-inch basalt stone, 12 inches in the ground marked with "¼" on west face and + on top, set by C. S. Nicklin in 1896. Notes call for ¼ on north face.

Replaced said stone with and deposited it alongside a 1x36-inch Galvanized iron pipe set 26 inches in the ground, with a 2½-inch diameter brass cap marked:

T32S  
¼S  
36  
R4W  
C.S.  
1986

The single remaining original bearing tree found:

- Douglas fir, 22-inch diameter, with healed blazes bears S5½°E, 159.53 feet to center of tree at lower blaze. Record: 155.76 feet.

The single remaining bearing tree recorded by F. Mench in 1913 found:

- Madrone 7-inch diameter, with scribed marked "BT" on exposed and rotted face bears S57°W, 135.66 feet to face. Record: 132.00 feet.

Mounded stones around corner and marked a new tree "CS" "BT":

- Douglas Fir, 17-inch diameter bears S58°W, 54.57 feet to center of tree at lower blaze.

Corner lies on steep, brushy, east slope and about 80 feet South of a draw course S57°E.

September 15, 1986  
T. Newcomb  
D. Edwards  
R. Romio

Edward McGinty  
County Surveyor

V = 21°

P. -251