

FIRST RE-ESTABLISHMENT

GCDB 100100

Township corner common to Townships 34 and 35 South, Ranges 1 and 2 West.

Set 1"x 36" galvanized iron pipe, 33" in the ground with a 2½" bronze cap stamped:

T. 34 & 35 S. R. 1 & 2 W
36 | 31
Sec. ——— Cor.
1 | 6
C.S.
1969

From which:

- The original bearing tree, (now a 27" White Oak with open rotted faces) bears N82°E, 62.0 feet to the upper face;
- The original bearing tree, (now a 16" White Oak with scribe marks visible) bears S37°E, 81.8 feet to the face of the upper blaze.
- The original bearing tree, (now a 22" White Oak with open and rotted upper face) bears S24½°W, 93.5 feet to the upper face.
- Oak remnants check record position of original Northwest bearing tree.

From said pipe corner, I establish the following new bearing trees:

- A 8" Yellow Pine, scribed "CS-BT" bears N69°E, 17.8 feet to the face of the lower blaze;
- A 12" Yellow Pine, scribed "CS-BT" bears N79°W, 82.8 feet to the face of the lower blaze;
- An 18" White Oak, scribed "CS-BT" bears S39¼°W, 97.3 feet to the face of the upper blaze.

June 11, 1969

G. Kaiser

G. Pinkham

Approved by:

Mark E. Boyden

County Surveyor