

FIRST RE-ESTABLISHMENT

GCDB 100300

Section corner common to Sections 24 and 25, Township 34 South, Range 2 West and Sections 19 and 30, Township 34 South, Range 1 West, W.M. $V = 20\frac{1}{2}^\circ$

Found, 1 inch diam. G.I. pipe, exposed 24 ins., with pot metal filled reducer marked:

T34S R1 & 2W	
24	19

25	30
1960	

Original BTs recorded by Ives and Hyde in 1854, found as follows:

- Black Oak snag, 13-inch diameter, with healed blazes, bears $N32^\circ E$, 56.4 feet to estimated lower face. Record, $N32^\circ E$, 56.76 feet.
- White Oak, 11-inch diameter, containing reverse impression of scribed "BT" in opened lower face, bears $S25^\circ E$, 48.1 feet to scribed face. Record, $S25^\circ E$, 48.18 feet.
- A dead and down Oak, containing scribe marks found at record location of original S.W. BT
- A stump hole found at record location of original N.W. BT

I marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- Cedar, 5-inch diameter, bears $N45\frac{1}{2}^\circ E$, 48.60 feet.
- Cedar, 4-inch diameter, bears $S55^\circ E$, 34.35 feet.
- Cedar, 6-inch diameter, bears $S76\frac{3}{4}^\circ W$, 12.05 feet.
- Cedar, 6-inch diameter, bears $N74\frac{1}{2}^\circ W$, 24.80 feet.

Corner lies about 75 feet East of small rocky draw.

July 29, 1975
Ed Graham
K. Weaver