

## FIRST RE-ESTABLISHMENT

GCDB 100640

Quarter corner to Section 1, Township 34 South 2 West & Section 6, Township 34 South 1 West.

Found the original witness tree (now a 20" Fir) plainly scribed which bears N11°E, 17.8 feet, and maple sprouts to conform to the location for the original SW witness tree.

From which evidence, set a 1"x 36" iron pipe 30" in the ground for corner.

From which:

- A 15" Fir, scribed CS-BT bears N65½°E 23.5 feet;
- A 7" Fir scribed CS-BT, bears S33½°W, 13.2 feet;

July 13, 1960  
M. E. Boyden  
F. A. Roberts  
C. L. Birk  
O. Blankenship

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 100640

Quarter corner common to Section 1, Township 34 South, Range 2 West and Section 6, Township 34 South, Range 1 West, W.M.

Found flush in ring of stone, a 2-inch diameter iron pipe, with 3¼-inch diameter standard BLM brass cap (not of record) marked:

T34S  
R2W R1W  
¼  
S1 | S6  
1973

Original bearing tree, recorded by Ives and Hyde in 1854 and reported on First Re-establishment, page 13, in 1960; now a fir snag, 17-inch diameter, containing scribed "¼" in partly exposed face, bears N11°E, 17.70 feet to scribed upper face. Record: 17.82 feet.

Bearing trees marked on First Re-establishment found:

- Douglas Fir, 21-inch diameter, with healed blazes bears Record: N65½°E, 23.5 feet (on slope) to estimated face. Re-measured 23.45 feet to center of tree at lower blaze.
- Douglas Fir, 13-inch diameter, with healed blazes bears Record: S33½°W, 13.20 feet to estimated face. Re-measured; 13.49 feet to center of tree at lower blaze.

**Note:** Removed the above-described monument and find the 1x36 ins galvanized iron pipe set on First Re-establishment inside the 2-inch diameter (BLM) pipe. Replace both monuments as found and mound stones around same.

Corner lies on steep (70%) East slope, an estimated 200 feet East of road (switch-back around rock quarry) and as estimated 200 feet West of stream.

**See also Jackson County Project File 86-68**

December 4, 1986  
R. Frost  
T. Newcomb

Edward McGinty  
County Surveyor

V = 18°  
P. -338