

FIRST RE-ESTABLISHMENT

GCDB 140100

Quarter corner common to Section 31, Township 34 South, Range 1 West, and Section 6, Township 35 South, Range 1 West, W.M.

Found projecting 5 ins. in mound of stone, a ½-inch diameter re-steel rod. This rod set by Edward McGinty (ORLS 301) in 1969 (from found original evidence; reverse impression of scribed "T") who double-blazed two reference trees as noted below.

Over this re-steel rod, I set a 1x36-inch G.I. pipe, 30 ins. in the ground with a 2½ ins. bronze disc marked:

Jackson County 1978
T34S R1W
31
¼S —
6
T35S R1W

Original bearing trees, recorded by Ives and Hyde in 1854, found as follows:

- White oak stump shell, 28-inch diameter, bears Record: N45°E, 18.48 feet to estimated face.

Reference trees, double blazed in 1969:

- White oak, 12-inch diameter bears S53°19'E, 73.35 feet to center of tree at lower blaze.
- Cedar, 10-inch diameter, bears N86°40'E, 108.46 feet to center of tree at lower blaze.

I mark a new tree "CS" "BT":

- White oak, 18-inch diameter, bears S14°E, 80.78 feet to center of tree at lower blaze.

Corner lies in large opening on NE slope.

For basis of bearing, see Jackson County project file No. 78-6.

May 4, 1978

B. Malotte

R. Frost

Witness: J. Coleman, resident

Approved by: Edward McGinty
County Surveyor