

## FIRST RE-ESTABLISHMENT

GCDB 200100

Section corner common to Sections 31 and 32, Township 34 Range 1 West and Sections 5 and 6, Township 35 South, Range 1 West.

For corner set a 1" x 36" galvanized iron pipe 32" in the ground with 2½" bronze cap stamped:

T34 & 35S, R1W	
Section cor.	
31	32
----- c.s.	
6	5
1964	

From which:

- The original bearing tree (now a 20" Yellow Pine, plainly scribed) bears North 50° West, 5.3 feet;
- The original bearing tree (now a 20" White Oak with two old scars and exposed faces rotted) bears South 82° West, 23.0 feet.

From said pipe corner, I establish the following new witness trees:

- An 8" Yellow Pine scribed "CS-BT" bears South 7½° West, 24.2 feet.
- A 12" Yellow Pine scribed "CS-BT" bears South 72½° East, 53.7 feet.
- A 6" Yellow Pine scribed "CS-BT" bears North 69° East, 41.2 feet.

November 10, 1964  
Lee D. Pinkham, Deputy County Surveyor  
Lloyd Hart

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 200100

Section corner common to Sections 5 and 6, Township 35 South, Range 1 West, and Sections 31 and 32, Township 34 South, Range 1 West, W.M.

Found projecting 2 ins., the 1-inch diameter galvanized iron pipe, with a 2½-inch diameter brass cap marked:

T34 & 35S R1W  
Section Cor.  
31 | 32  
—+—  
6 | 5  
1964

As recorded on First Re-establishment, page 15, in 1964.

Original bearing trees, recorded by Ives & Hyde in 1854 found as follows:

- Hollow White Oak, 20-inch diameter, with axed and/or rotted out faces, located on Southwesterly bearing fence line, bears as reported in 1964; S82°W, 23.0 feet to estimated face. Re-measured 23.65 feet to center of tree near base.
- Ponderosa Pine, 21-inch diameter, located at the corner of North and East-West fence lines and containing scribe marks in axed into and partly rehealed upper face, bears as recorded in 1854; N50°W, 5.28 feet to scribed upper face. Re-measured 5.80 feet to center of tree at lower blaze.

Bearing trees marked on First Re-establishment found and measured to partly exposed lower face(s):

- Ponderosa Pine snag, now 8-inch diameter with scribed faces, bears Record: N69°E, 41.2 feet.
- Ponderosa Pine snag, now 13-inch diameter, with scribed faces, bears Record: S72½°E, 53.7 feet.
- Ponderosa Pine, now 10-inch diameter with scribed faces, bears Record: S7½°W, 24.2 feet. Re-measured 24.5 feet to center of tree at lower blaze.

Mark new trees "CS" "BT" and take measurements to center of trees at lower blaze:

- White Oak, 4-inch diameter, bears N29°E, 14.4 feet.
- White Oak, 4-inch diameter, bears S49°E, 28.8 feet.

Corner lies 2½ feet South of East-West fence line.

September 16, 1987  
R. Frost, Tech.  
S. Beecher, Tech.

Edward McGinty  
County Surveyor

V = 17½°  
P. 331-332