

FIRST RE-ESTABLISHMENT

GCDB 200200

Corner common to Sections 29, 30, 31 and 32, Township 34 Range 1 West.

Set a 1"x 36" galvanized iron pipe 30" in the ground with a 2½" bronze cap stamped:

| | | | |
|-----|------|-----|------|
| | T34S | R1W | |
| | 30 | 29 | |
| Sec | 31 | 32 | Cor. |
| | C.S. | | |
| | 1967 | | |

From which:

- A 12" White Oak, plainly scribed, bears North 38° East, 16.5 feet to the face of the lower blaze;
- A 35" White Oak shell bears South 37° West, 17.6 feet to probable upper face;
- A 31" White Oak, center rotted, bears South 3° East, 32.9 feet to the face of the lower blaze; stump hole and remains of an oak tree checks for the Northwest tree.

Marked the following new trees:

- A 10" White Oak, scribed CS-BT, bears North 54¾° West, 55.3 feet to the face of the lower blaze;
- An 8" White Oak, scribed CS-BT, bears South 55° West, 29.1 feet to the face of the lower blaze;
- A 22" White Oak, scribed CS-BT, bears South 78¼° East, 22.9 feet to the face of the upper blaze.

November 10, 1967
F. A. Roberts
Jack Huston

Approved By:
L. D. Pinkham,
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT
GCDB 200200

Section corner common to Sections 29, 30, 31 and 32 of Township 34 South, Range 1 West, W.M.

Found at corner position, pushed over, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1st Re-establishment in 1967 and marked:

T34S R1W
30 | 29
Sec —|— Cor
31 | 32
C.S.
1967

Reset to correct location using existing evidence exposed 4 ins. in mound of stones.

Original bearing trees recorded by Ives and Hyde of the GLO in 1854 found and measured to center at base:

- W. oak now 13 ins. diam. with a partially healed blaze with weathered face brs. N38°E, 17.0 ft. record; 16.5 ft. to face .
- W. oak rotted shell brs. S37°W, 18.7 ft. Record 17.6 ft. to estimated face.
- W. oak rotted shell brs. S3°E, 33.8 ft. record; 32.9 ft. to estimated face.

Bearing trees recorded on said 1st re-establishment found with healed double blazes and measured to center at lower blaze:

- W. oak now 11 ins. diam. brs. record; N54¾°W, 55.3 ft.
- W. oak now 11 ins. diam. brs. record; S55°W, 29.1 ft.
- W. oak now 23 ins. diam. brs. record; S78¼°E, 22.9 ft.

Corner lies approx. 450 ft. south of private gravel road.

December 16, 2008

B. Beeman

H. Durkee

Roger R. Roberts

Jackson County Surveyor

P. – 236

V – 15°40'