

## FIRST RE-ESTABLISHMENT

GCDB 200300

Section corner common to Sections 19, 20, 29 and 30, Twp. 34 South, Range 1 West, W.M.

Found projecting 2 ins. from concrete, 0.35 feet Southerly of the metal fence post corner of North and East bearing fence lines, the  $\frac{5}{8}$  ins. iron pin, set on survey no. 3736 in 1968.

I place yellow plastic cap on said pin marked: "JACKSON C.S." From which:

- White Oak, 6-inch diameter (double blazed and recorded on above noted survey) with healed blazes bears Record: S75°3/4 of tree.

Original bearing trees recorded by Ives and Hyde in 1854 found as follows:

- White Oak, 20-inch diameter, with multiple blazes and grown over tobacco can in Northeast side, bears S50°E, 67.25 feet, to center of tree at lower blaze, Record: S52°E, 67.98 feet.
- The center of the stump remains of a down and rotted pine containing scribe marks, including "34 S30" and "BT" bears S85°W, 67.26 feet. Record: S85°W, 66.66 feet.
- White Oak, 18-inch diameter, with healed blazed and rotted interior, bears N18°15'W, 63.22 feet to center of tree at lower blaze. Record: N18°W, 62.70 feet.

I mark new trees CS BT and take measurements to center of trees at lower blaze:

- White Oak, 9-inch diameter, bears S78°E, 28.3 feet.
- White Oak, 8-inch diameter, bears S79°30'W, 53.35 feet.
- Easterly branch, 8-inch diameter of a double White Oak, bears N16°45'W, 23.8 feet.

April 9, 1979

B. Malotte

R. Frost

Approved by: Edward McGinty  
County Surveyor