

FIRST RE-ESTABLISHMENT

GCDB 200440

Quarter corner between Sections 17 and 18, Township 34 South, Range 1 West.

Found original BTs plainly scribed, both trees dead.

Set a 1"x 36" galvanized pipe for corner.

From which:

- A 24" Black oak scribed C.S.-BT bears S.46°W., 102.1 feet.
- A 14" Black oak scribed C.S.-BT bears N.76°15'E., 168.2 feet.

March 20, 1931
C. Z. Boyden,
Deputy County Surveyor

Tice and Pettegrew, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200440

Quarter corner common to Sections 17 and 18, Township 34 South, Range 1 West, W.M.

At the corner, found flush in ring of stones the 1-inch diameter galvanized iron pipe set on First Re-establishment, page 5, in 1931.

In the top of said pipe, in cement, set a 2½-inch diameter brass cap marked:

T34S R1W
S
18 | 17
C.S.
1981

Bearing trees recorded on First Re-establishment found and measurements taken to center of trees at lower blaze:

- Black Oak, 18-inch diameter, with healed blazes, bears N79°49'E, 169.88 feet (not visible from corner; course and distance computed) Record: N76°15'E, 168.2 feet.
- Black Oak, 30-inch diameter, with healed blazes bears S46°W, 102.16 feet. Record: 102.1 feet.

Corner lies about 200 feet North of location marker on 8-inch diameter Pine, alongside Longbranch Road.

July 7, 1981
R. Frost
R. Templin

Edward McGinty
County Surveyor

P.-105

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 200440

Quarter corner common to Sections 17 and 18, Township 34 South, Range 1 West, W.M.

Found projecting 2 ins. in a small mound of stone the 1 in. diam. galvanized iron pipe set on First Re-establishment, in 1931; with a 2½ ins. brass cap set on Second Re-establishment, in 1981 marked:

T34S R1W
¼S
18 | 17
CS
1981

Bearing trees marked on First Re-establishment found:

- Sawed Black Oak stump, 33-inch diameter, with healed blazes, bears S46°W, 102.64 feet to center of tree at lower blaze. Record: 102.10 feet to estimated face.
- Northeast bearing tree still in good condition but not visible from corner because of heavy brush.

Marked new trees "CS" "BT" and take measurements to the center of tree at lower blaze:

- Madrone 6-inch diameter bears N18°E, 38.86 feet.
- Black Oak 6-inch diameter bears S2¼°W, 34.24 feet.

Set 5/8 x 12 ins. rebar with yellow plastic caps marked "Jackson CS" flush and on line with new bearing trees:

- N18¼E, 38.00 feet.
- S2¼°W, 33.55 feet.

Corner lies on Southwest slope. There is a new trailer house west and a shop building north of sawed black oak bearing tree.

September 9, 1991
T. Newcomb, Tech.
H. Durkee, Tech.

Verlyn Thomas
County Surveyor

V = 18°