

FIRST RE-ESTABLISHMENT

GCDB 300200

Section corner common to Sections 28, 29, 32 and 33, Township 34 South, Range 1 West.

Found a 2" x 36" galvanized iron pipe for corner, the original BT to the northeast (with scribe legible) checks the official government record.

From which corner a X chiseled on top of the southerly end of a solid rock outcropping bears East 30.3 feet.

- An 8" black oak scribed C.S.-BT bears S33°5'E 43.1 feet.
- A 20" cotton wood scribed C.S.-BT bears S27°00'W 46.2 feet.
- A 6" alder scribed C.S.-BT bears N72°15'W 39.3 feet.

October 26, 1937
C. Z. Boyden,
Deputy County Surveyor
C. I. Bourne

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 300200

Section corner common to Sections 28, 29, 32 and 33, Township 34 South, Range 1 West, W.M.

At the corner, found 2 ins. deep, the 2-inch diameter iron pipe set on First Re-establishment, page 2, in 1937.

In the top of said pipe in cement, set a 2½-inch diameter brass cap Marked:

T34S	R1W
29	28
<hr/>	
32	33
C.S.	
1981	

From which:

- A found cross in top of the Southerly end of rock outcrop located at end of farm road c. Northerly, bears Record: East, 30.30 feet. In the center of found cross, set hub tack in lead filled drill hole.

Mark new trees "C.S." "BT" and take measurements to center of trees at lower blaze:

- White Oak, 10-inch diameter, bears S60°E, 36.88 feet.
- Alder, 8-inch diameter, bears S2°E, 102.10 feet.

Corner lies about 85 feet S65°W from the foot of rock ridge, an estimated 60 feet high, c. N45°W.

July 9, 1981
R. Frost
R. Templin

Edward McGinty
County Surveyor

V = 20°
P.-107

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 300200

Section corner common to Sections 28, 29, 32 and 33, Township 34 South, Range 1 West, W.M.

Corner described on Second re-establishment, page 52, dated 1981, has been removed by the construction of a waterline.

From the following evidence set a 1 x 30 ins. flanged galvanized iron pipe 24 ins. in the ground with attached 2½-inch diameter brass cap marked:

T34S R1W	
Jackson County Surveyor	
29	28

32	33
C.S.	
1993	

Poured concrete around monument.

Lead and tack set on Second re-establishment in the center of found “+” marked on First re-establishment, page 2, dated 1937, bears record East, 30.30 feet.

Single remaining bearing tree marked on Second re-establishment found:

- A White Oak, 10-inch diameter, healed blazes, bears S60°20' E, 36.88 feet to center of tree at lower blaze.

Marked new trees “CS” “BT” and take measurements to the center of tree at lower blaze:

- Alder, 12-inch diameter in a cluster of 4, bears S11°30'W, 281.06 feet.
- Ponderosa Pine, 13-inch diameter, bears N34°40' W, 168.25 feet.

Corner lies 15 feet East of low earth dam at south end of holding pond and 15 feet west of dirt road.

June 28, 1993
T. Newcomb, Tech.
J. Burgess, Tech.

Verlyn Thomas
County Surveyor

P.-96

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

FOURTH RE-ESTABLISHMENT

GCDB 300200

Section corner common to Sections 28, 29, 32 and 33, Township 34 South, Range 1 West, W.M.

Found corner monument destroyed.

From the following evidence, re-set at the corner position, level with the road and in a 16-inch square x 1-foot deep concrete slab, a 1x30-inch flanged galvanized iron pipe with attached 2½-inch diameter brass cap marked:

JACKSON COUNTY SURVEYOR
T34S R1W
S29 | S28
—+—
S32 | S33
2002

Bearing trees and references recorded on Third Re-establishment, found and re-measured:

- Lead and tack set in rock out-cropping on Second Re-establishment bears record, East 30.30 feet.
- White Oak, now 11-inch diameter with healed blazes, marked on Second Re-establishment bears record, S 60°20' E, 36.88 feet to center of tree at lower blaze.
- Ponderosa Pine, now 14-inch diameter with healed blazes, marked on Third Re-establishment, bears N 34°06'40" W, 168.15 feet to center of tree at lower blaze. Record: N 34°40' W, 168.25 feet.
- Alder, now 14-inch diameter with partially healed blazes, marked on Third Re-establishment (not usable, due to inaccessibility).

Take new reference, a concrete nail and shiner set in rock out-cropping bears S 35°41'30" E, 42.77 feet.

Corner lies 16 feet west of center of granite road and 3.2 feet west of steel fence post with location marker.

March 19, 2002

H. Durkee

T. Newcomb

Roger Roberts

Jackson County Surveyor

P.-40