

## FIRST RE-ESTABLISHMENT

GCDB 300300

Corner to Sections 20, 21, 28 and 29.

Found three original BTs.

Set 2"x36" galvanized pipe for corner:

- Scribed 30" White Oak C.S.-BT which bears N.76°E., 127.2 feet.
- Scribed 14" White Oak C.S.-BT which bears S.50°W., 93.8 feet.
- Scribed 4" White Oak C.S.-BT which bears S.10°30'E., 32.8 feet.
- The original BT bears N. 62°0'W., 56.3 feet.

February 19, 1929  
Boyden, Deputy County Surveyor  
Tice & Judd, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 300300

Section corner common to Sections 20, 21, 28 and 29, Township 34 South, Range 1 West, W.M.

At the corner found flush with the ground, the 2-inch diameter iron pipe, set on First Re-establishment, page 4, in 1929.

In the top of said pipe in cement, set 2½-inch diameter brass cap marked:

T34S R1W	
20	21
29	28
C.S.	
1981	

Original bearing trees recorded by Ives and Hyde in 1854 found:

- White Oak, 23-inch diameter with (re)healed blazes bears S26°45'W, 41.5 feet to center of tree. Record: S28°W, 40.92 feet.
- The most Southerly branch, 17-inch diameter, of a double White Oak, bears N62°W, 56.7 feet to center of branch at lower blaze. Record: N61°W, 56.10 feet.

Bearing trees marked on First Re-establishment found and measurements taken to center of trees at lower blaze:

- White Oak, 11-inch diameter, with healed blazes, bears S10°10'E, 33.00 feet. Record: S10°30'E, 32.8 feet.
- White Oak, 18-inch diameter, with healed blazes, bears S50°W, 93.9 feet. Record: 93.8 feet.

Mark a new tree "CS" "BT":

- Ponderosa Pine, 14-inch diameter, bears N41°30'W, 32.30 feet to center of tree at lower blaze.

Corner lies alongside wood post corner of North and East bearing fence lines at North edge of dirt road c. East-West.

July 7, 1981  
R. Frost  
R. Templin

Edward McGinty  
County Surveyor

V = 18°  
P.-106