

FIRST RE-ESTABLISHMENT

GCDB 300340

Quarter corner to Sections 20 and 21, Township 34 South, Range 1 West.

Found stake set for corner; also both BTs plainly scribed. BT to SE dead.

Set a 1"x 36" galvanized pipe for corner.

From which:

- The original BT a 12" White oak bears N.57°W., 37.6 feet.
- Scribe a 10" White Oak C.S.-BT which bears S11°15'E., 66.0 feet.

April 14, 1931
C. Z. Boyden,
Deputy County Surveyor
Leland Pettegrew, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 300340

Quarter corner common to Sections 20 and 21, Township 34 South, Range 1 West, W.M.

At the corner found projecting 2 ins., the 1-inch diameter pipe set on the First Re-establishment, page 5, in 1931.

In top of said pipe, in cement, set a 2½-inch diameter brass cap marked:

T34S R1W
¼S
20 | 21
C.S.
1981

From which

- The only remaining original bearing tree recorded by Ives and Hyde in 1854, a White Oak, now 14-inch diameter with healed blazes bears N57°W, 37.80 feet to center of tree at lower blaze. Record: 37.62 feet.
- Bearing tree recorded on First Re-establishment, a White Oak, now 16-inch diameter with healed blazes bears S11°15'E, 66.55 feet to center of tree at lower blaze. Record: 66.0 feet.

Corner lies 4 feet West of North-South fence line and S52°E, an estimated 100 feet from Southeast corner of wood frame residence #5744 Rogue River Drive.

July 7, 1981
R. Frost
R. Templin

Edward McGinty
County Surveyor

V = 20°
P.-106