

**FIRST RE-ESTABLISHMENT**

**GCDB 300600**

Section corner common to Sections 4, 5, 8 and 9, located in Township 34 South, Range 1 West, W.M.

Found projecting 3 ins., the 1-inch diameter iron pipe with unmarked 2½-inch diameter brass cap set by this office, see corner report (page 112), dated 1970. Stamp cap:

T34S R1W	
5	4
8	9
C.S.	
1987	

Original bearing trees marked by Ives and Hyde in 1854 found as follows:

- Broken Black Oak stump bears Record: S76°E, 27.06 feet to estimated face; 27.4 feet to center.
- Oak stump shell bears Record: S75°W, 24.42 feet.
- Oak snag with rotted interior bears N76°W, 23.7 feet (record 23.1 feet.)
- Oak fragments found at record N43°E, 27 feet.

Trees marked by Jackson County in 1970 measured to center of tree at lower blaze:

- Ponderosa Pine 10-inch diameter with "BT" visible in partially healed lower blaze bears N64½°E, 14.1 feet.
- White Oak, 5-inch diameter, with double healed blaze, bears S43°E, 31.8 feet.
- Ponderosa Pine 8-inch diameter with double healed blaze bears S84°W, 24.65 feet.
- White Oak, 7-inch diameter with double healed blaze bears N10½°W, 31.4 feet.

5/8-inch diameter iron pin set on Survey No. 4406 was not found.

Corner lies on gentle (21%) north slope, 18.5 feet South of old partially down East-West fence line.

January 9, 1987  
R. Romio  
D. Edwards

Edward McGinty  
County Surveyor

V = 18°  
P.-28