

## FIRST RE-ESTABLISHMENT

GCDB 300640

Quarter corner common to Sections 4 and 5, Township 34 South, Range 1 West, W.M.

From the following original evidence at the location described below, set a 1x36-inch Galvanized iron pipe, 5 ins. in the ground to bedrock in a large mound of stones. In the top of said pipe, set in concrete, a 2½-inch diameter brass cap marked:

T34S R1W  
¼S  
5 | 4  
C.S.  
1986

Original bearing trees recorded in 1854 by Ives and Hyde found:

- A White Oak, now 30-inch diameter with scribe marks including "BT" and chaining notch visible in opened lower face, bears Record: S85°E, 44.22 feet to said chaining notch.
- Stump hole of a down Yellow Pine with axe mark visible bears Record: N87°W, 27.7 feet.

A 5/8-inch diameter iron rod set on Survey No. 4806 and referred to on Survey No. 4814, protruding 16 inches, bears N19°E, 2.30 feet.

A White Oak, now 9-inch diameter with double healed blazes, reported marked on Survey No. 4814, bears S10¾°E, 50.75 feet to center of tree at lower blaze.

Take new reference:

- A White Oak, 8-inch diameter scribed "CS" "BT", bears N59½°E, 39.60 feet to center of tree at lower blaze.

Corner lies in an opening, on a 12% southeasterly slope, an estimated 90 feet. South of a wire fence bearing East and West.

September 25, 1986  
D. Edwards  
T. Newcomb

Edward McGinty  
County Surveyor

V = 20°  
P.-257