

**GCDB 320200**

West 1/16 Section corner common to Sections 28 and 33, Township 34 South, Range 1 West, W.M.

Set a double barreled 12 gauge muzzle loading shot gun barrel 32 ins. long, 28 ins. in the ground for corner, midway between the first ¼ Section corner to the east and the first section corner to the west as determined by Recorded Survey #987,

From the said shot gun barrel for corner:

- A 10 ins. White Oak scribed "1/16 BT" bears S43½°E, 16.1 feet.
- Scribe a 12 ins. White Oak "1/16 BT" which bears N40°E, 19.9 feet.

A ¾ x 26 ins. iron bolt bears East along the Section line 24.3 feet.

April 11, 1957  
C. Z. Boyden  
C.L. Birk

**SEE NEXT PAGE FOR CORRECTED LOCATION**

## CORNER CORRECTION

GCDB 320200

CORRECTION of the West 1/16 Section Corner to Sections 28 and 33, Township 34 South, Range 1 West, W.M.

Found an error in the calculation for setting this corner from the random traverse hub set on Recorded Survey No. 987.

Found the said hub, iron bolt and shotgun barrel monuments, resetting the shotgun barrel S89°53'E, 5.00 feet on the Section line from where it was originally set on the establishment of April 11, 1957.

From which:

- The said  $\frac{3}{4}$  x 26 ins. bolt bears Easterly on the Section line 19.3 feet.
- The previously scribed 10 ins. White Oak bears S25°E, 13.2 feet.
- The previously scribed 12 ins. White Oak bears N28°E, 17.2 feet.

June 6, 1959  
M. E. Boyden  
C. L. Birk

SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT

## FIRST RE-ESTABLISHMENT

GCDB 320200

West Sixteenth corner common to Sections 28 and 33, Township 34 South, Range 1 West, W.M.

Found projecting 7 ins. the double barrel of a 12 gauge muzzle loader 28 ins. long, with 6 ins. broken off. Replaced found monument with a 1 x 36-inch Galvanized iron pipe set 22 ins. in the ground with a mound of stone around corner.

Bearing trees marked on First establishment dated 1959 found with healed blazes and measured to estimated faces:

- White Oak, 14-inch diameter, bears Record: N28°E, 17.2 feet. Re-measured 17.50 feet to center.
- White Oak, 12-inch diameter, bears Record: S25°E, 13.20 feet. Re-measured 13.60 feet to center.
- $\frac{3}{4}$  ins. bolt head flush bears Record: easterly 19.30 feet. The bearing easterly was recorded because of a White Oak on line between the bolt and corner.

Marked new tree "CS BT":

- White Oak, 14-inch diameter, bears East 1.95 feet.

Corner lies North 20 feet from cleared field at the edge of oak timber.

June 25, 1993  
T. Newcomb, Tech.  
J. Burgess, Tech.

Verlyn Thomas  
County Surveyor

V = 17½°  
P.-95